PP1 COMPRESSOR CONFIGURATION

Who fills in?

Company name:

Select compressor model (L + H motor)

Select compressor model

Standard Extent of Delivery: •suction & discharge shut-off valve •pressure relieve valve •sight glass •lubrication oil charge •motor PTC temperature sensor •motor protector (to be mounted in separate box) •IP54 electrical box •nitrogen protection •kit bridges D.O.L. start •spring vibration dampers (4&6 cyl.) •rubber vibration dampers (8 cyl.)

Motor voltage:

- ◯ **400/3/50Hz - 460/3/60Hz PW (standard)**
- ◯ **Motor with special voltage (contact SRMTec)**

Additional accessories

- ☐ Motor with special voltage
- ☐ Motor with DUAL voltage
- ☐ Start unloader device (SU)+ discharge temperature sensor (from 4 cyl.)
- ☐ Crankcase heater
- ☐ Opto-electronic oil level sensor*
- ☐ Oil service valve*

**If needed, select only 1 option*

- ☐ 1 x Capacity control head with coil (from 4 cyl.)
- ☐ 1 x Capacity control head with Atex coil (from 4 cyl.)
- ☐ 2 x Capacity control head with coil (from 6 cyl.)
- ☐ 2 x Capacity control head with Atex coil (from 6 cyl.)
- ☐ Additional fan (4&6 cyl.)

- ☐ Discharge temperature sensor
- ☐ Oil & Gas equalizing fittings for parallel operation
- ☐ Rubber vibration dampers
- ☐ Version with oil pump (F)
- ☐ Electronic oil pressure safety switch (for oil pump)
- ☐ Special wooden package

Customer Notes