RP1 COMPRESSOR CONFIGURATION

Who fills in?

Company name:

Select compressor model (L + H motor)

Select compressor model

Standard Extent of Delivery: •suction & discharge shut-off valve •pressure relieve valve •sight glass •lubrication oil charge •motor PTC temperature sensor •nitrogen protection •motor protector INT69B2 •IP54 electrical box •D.O.L. starting connection •spring vibration dampers (4&6 cyl.) •rubber vibration dampers (8 cyl.)

Motor voltage:

- ◉ **400/3/50Hz - 460/3/60Hz PW (standard)**
- ○ **Special voltage (contact SRMTec)**

Additional accessories:

- ☐ Motor with special voltage
- ☐ Motor with DUAL voltage
- ☐ Start unloader device (SU) (4&6 cyl.)
- ☐ Crankcase heater
- ☐ Oil service valve*
- ☐ Opto-electronic oil level sensor*
- ☐ 1 x Capacity control head with coil (from 4 cyl.)
- ☐ 2 x Capacity control head with coil (6&8 cyl.)
- ☐ Liquid injection kit with LCM module
- ☐ Electronic oil pressure safety switch (for oil pump)
- ☐ Discharge temperature sensor
- ☐ Oil&Gas equalizing fittings for parallel operation
- ☐ Additional fan (4&6 cyl.)
- ☐ Special wooden package
- ☐ Version with oil pump (-F)
- ☐ Rubber vibration dampers (4&6 cyl.)

**If needed, select only 1 option*

Customer Notes: